Bess' Flower Garden

Courthouse Steps Wall Hanging

Finishes to 28½" × 28½"

REQUIRED MATERIALS....

- $3\frac{1}{2}$ " × 14" dark red for **Center Square** and **cornerstone**
- 1/8 yard cream for Round 1 Light and sashing
- 2½" × WOF for Round 2 Light
- ½ yard cream for Round 3 Light and outer border
- 1/8 yard cream for Round 4 Light
- 21/2" × WOF red for **Round 1 Dark**
- 2½" × WOF red for **Round 2 Dark**
- 2½" × WOF red for Round 3 Dark
- 1/8 yard red for Round 4 Dark
- 2½" × WOF blue for **Round 1 Dark**
- 2½" × WOF blue for **Round 2 Dark**
- 2½" × WOF blue for **Round 3 Dark**
- 1/8 yard blue for Round 4 Dark
- ½ yard red for inner border and binding
- 1 yard for **backing**
- Creative Grids 10" Log Cabin Trim Tool Duo #CGRJAW10

RECOMMENDED PRODUCTS_____

- Olfa Rotary Cutter
- Olfa Spinning Rotary Mat 12" × 12"

Make Courthouse Steps Blocks_____


Follow the instruction pamphlet that comes with the 10" Log Cabin Trim Tool Duo to make (4) Courthouse Steps Blocks.

Each block should measure $10\frac{1}{2}$ " × $10\frac{1}{2}$ ".

PLEASE NOTE: If you are confident with your ¼" seam allowance, and prefer to cut your courthouse steps "logs" to the exact length instead of cutting them longer and trimming, refer to the "Sewing and Trimming Sequence" download available on the Creative Grids website (see link at right).

PLEASE NOTE.....

All seam allowances are 1/4" WOF = Width of Fabric



Follow along with the HOW TO MAKE A
COURTHOUSE STEPS
BLOCK WITH CREATIVE GRIDS
LOG CABIN TOOL
video featured on our YouTube channel:

YouTube.com/Shabby Fabrics

For Creative Grid's

Sewing and Trimming

Sequence

go to:

creativegridsusa.com/products/ CGRJAW10

and click the "Instructions" button.

CUT FABRICS FOR FINISHING

From Center Square and cornerstone fabric, cut:

• (1) $1\frac{1}{2}$ " × $1\frac{1}{2}$ " square for **cornerstone**

From Round 1 Light and sashing fabric, cut:

• (4) $1\frac{1}{2}$ " × $10\frac{1}{2}$ " strips for **sashing**

From **inner border** and **binding** fabric, cut:

- (4) 2½" × WOF strips for **binding**
- (4) 1½" × WOF strips for inner borders

From Round 3 Light and outer border fabric, cut:

• (4) 3" × WOF strips for **outer borders**

Assemble Wall Hanging

Arrange blocks, referring to sample image for placement and orientation.

Sew blocks and **sashing** strips together in rows. Press toward sashing.


Sew a sashing strip to each side of the **post**. Press toward sashing. This is your horizontal sashing unit.

Join Row 1, horizontal sashing unit, and Row 2, pressing seams open.

For remaining steps, press all seams to the outer border of the wall hanging.

Sew **inner border** strips to the left and right sides of the wall hanging, and trim to be even with the wall hanging. Sew inner border strips to the top and bottom of the wall hanging, and trim to be even with the wall hanging.

Sew **outer border** strips to the left and right sides of the wall hanging, and trim to be even with the wall hanging. Sew outer border strips to the top and bottom of the wall hanging, and trim to be even with the wall hanging.



FINISH WALL HANGING__

Layer wall hanging top, batting, and backing. Quilt as desired.

Sew **binding** together into one long strip. Fold binding in half lengthwise with wrong sides together and press. Sew the binding to the front side of the wall hanging starting at any side. Turn the binding over and hand stitch to the back of the wall hanging.

Shop online 24/7 for Kits, Patterns, BOMs, Clubs and more at Shabby Fabrics.com